



OptoTech

FLASH Twin-A

Digital Surfacing Machine




The new digital surfacing-turning machine FLASH Twin-A is an enhancement of our tried and tested FLASH series. Due to the usage of 2 Fast Tools, the FLASH Twin-A is able to simultaneously process 2 freeform lenses. Considerably increased speed of the tool spindles, combined with a high-class precision ball bearing, leads to significant improvements in quality and quantity. It is the ideal complement to our ESM Twin-A.



Technical data

	FLASH Twin-A
Application	Digital Surfacing-Turning Machine
Lens Diameter	51 mm - 85 mm
Working Range Radius cv	Turning -15 dpt.
Working Range Radius cx	Turning +25 dpt.
Control	Beckhoff high resolution real-time continuous path control 15" touch screen with interactive user interface
Lens Material	All organic Materials
Number of Fasttools	2
Productivity	60 lenses/h - 120 lenses/h; depending on process
Tools	Turning Tools 1 and 2: PCD R5.5 mm and Natural diamond tool R2.0 mm
Workpiece Spindles	Drive: Direct driven with high precision ball bearing concept; Interface: Collet Chuck \varnothing 43 mm DIN 58766
Air Pressure Requirement	6 bar
Power Requirement (others on request)	400 V / 50 Hz
Dimensions	Width: 1785 mm, Height: 1940 mm, Depth: 2380 mm
Weight (approx.)	2200 kg
Disclaimer	All data are subject to change without notice. Please verify details with OptoTech.





Highlights

- Due to the usage of 2 Fasttools, the FLASH Twin-A is able to simultaneously process 2 freeform lenses
- Considerably increased speed of the tool spindles, combined with a high precision ball bearing for the workpiece spindles, leads to significant improvements in quality and quantity
- A high dynamic drive concept combined with an ultrafast computer controller enable highest precision in freeform surfacing within shortest processing times
- For processing backsideprogressive, atoric, individual, front progressive and standard toric surfaces
- Optimized automatic loading system
- Lowest vibration due to OptoTech async mode
- Machine base made of rigid mineral cast
- FastTool highspeed linear drive
- Ideal combination with ESM Twin-A

Performance characteristics

- Cut-to-polish (spherical, torical or a-torical): approx. 120 surfaces/h
- Cut-to-polish (freeform): approx. 120 surfaces/h

Options

- Coolant tank
- Barcode hand scanner
- Remote diagnosis
- LAN connection