



OptoTech

SWARFMASTER

OptoTech Pre-Grinding System for Standard Rx and Freeform Lenses




The Rx-lens production of the future will significantly change all operations and processes. As an entry-level concept for automatic Rx production 2.0, OptoTech developed the new SWARFMASTER for high-performance pre-grinding of mineral and organic lenses (toric and freeform). By separating the pre- and fine grinding processes, you optimize your production and ultimately increase the performance and quality of your surfacing machines for mineral lenses and glass molds as well as organic lenses.



OptoTech

Données techniques

	SWARFMASTER
Lens Diameter	51 mm - 85 mm
Working Range Radius cc	Mineral: up to -16 dpt. (Index 1.523)
Working Range Radius cc	Organic: up to -15 dpt. (up to -22 dpt. with Ø45mm PCD tool)
Working Range Radius cx	+30 dpt.
Lens Material	All Material
Productivity	200 lenses/h
Productivity	60 lenses/h - mineral glass (depending on production mix)
Workpiece Spindle	Drive: Direct driven async motor with ball bearings; Interface: Collet chuck ø43 mm DIN 58766
Air Pressure Requirement	6 bar
Power Requirement (others on request)	400 V / 50 Hz
Dimensions	Width: 1365 mm, Height: 2076 mm, Depth: 1865 mm
Weight (approx.)	1250 kg





Highlights

- The SWARFMASTER is the ideal pre-cutter for all grinding and turning machines (mineral and organic lenses)
- Significant increase in grinding, turning and polishing capacity by adding the SWARFMASTER
- Can be used to replace old existing traditional mineral pre-grinding machines
- Usage of high-performance tools (diamond grinding wheel Ø66 R4 for mineral lenses and PCD Tool ø66mm R6 HSK with 15 cutters for organic lenses)
- Adaptive toolwear: Implementation of wear improvement. Machine calibrates itself from glass to glass
- Automatic tool clamping system for quick tool change. Fastest workpiece change system due to optimized automatic handling module.
- Modular setup of the most important service parts for fastest maintenance

System Advantages

- Overall optimization of production output
- Increased processing capacity
- Improving performance & quality of surfacing machines
- Improved chip management

Performance Characteristics

Application area: mineral lenses, glass molds and organic lenses. Backside progressives; Atorical; Individual; Front progressive; Standard toric; Blended lenses

- Mineral freeform milling of up to 60 lenses/h (depending on production mix)
- Organic freeform milling of up to 200 lenses/h (depending on production mix)

Options

- Automatic and manual version with smallest footprint available
- Barcode hand scanner
- Remote diagnostic
- LAN connection